Safety Data Sheet

Helium

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SDS Reference Number: EST-He-061A

Issue date: 2/16/2023 Revision date: 6/13/2025 Supersedes version of: 2/16/2023 Version: 2.0

Warning



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : Helium EST-He-061A SDS no Other means of identification Helium

> CAS-No. : 7440-59-7 EC-No. : 231-168-5 EC Index-No.

REACH registration No Listed in Annex IV / V REACH, exempted from registration.

Chemical formula

1.2. Relevant identified uses of the substance or mixture and uses advised against

: Industrial and professional uses. Perform risk assessment prior to use. Relevant identified uses

Consumer use. Test gas/Calibration gas. Laboratory use. Purge gas, diluting gas, inerting gas.

Shield gas for welding processes.

Use for manufacture of electronic/photovoltaic components. Contact supplier for more information on uses.

Uses advised against Do not inhale product on purpose because of the risk of asphyxiation.

Uses other than those listed above are not supported, contact your supplier for more information

on other uses.

1.3. Details of the supplier of the safety data sheet

Flme Messer Gaas AS

Kopli 103 11712 Tallinn Estonia T +372 6102001

info@elmemesser.ee, www.elmemesser.ee

1.4. Emergency telephone number

Emergency telephone number Mürgistusteabekeskus, Terviseamet: tel. 16662, (24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP] Physical hazards Gases under pressure: Compressed gas

H280

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP) Warning

Hazard statements (CLP) H280 - Contains gas under pressure; may explode if heated. Precautionary statements (CLP)

: P403 - Store in a well-ventilated place. - Storage

Supplemental information Do not inhale product on purpose because of the risk of asphyxiation.

Asphyxiant in high concentrations.

2.3. Other hazards Not classified as PBT or vPvB.

The substance/mixture has no endocrine disrupting properties.

Not classified as PMT or vPvM.

Safety Data Sheet

Helium

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 SDS Reference Number: EST-He-061A

3.1. Substances

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP] ATE, EUH-statements, M-Factors
Helium	CAS-No.: 7440-59-7 EC-No.: 231-168-5 EC Index-No.: REACH registration No: *1	100	Press. Gas (Comp.), H280

Contains no other components or impurities which will influence the classification of the product.

*1: Listed in Annex IV / V REACH, exempted from registration.

SECTION 3: Composition/information on ingredients

*3: Registration not required: Substance manufactured or imported < 1t/y.

3.2. Mixtures Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim

warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.

- Skin contact
 - Eye contact
 - Ingestion
 - Adverse effects not expected from this product.
 - Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

In high concentrations may cause asphyxiation. Symptoms may include loss of

mobility/consciousness. Victim may not be aware of asphyxiation.

See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.

Product does not burn, use fire control measures appropriate for the surrounding fire.

- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

Specific hazards : Exposure to fire may cause containers to rupture/explode.

Hazardous combustion products : None.

5.3. Advice for firefighters

Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation

may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage

systems.

If possible, stop flow of product.

Use water spray or fog to knock down fire fumes if possible.

Move containers away from the fire area if this can be done without risk.

Special protective equipment for fire fighters : In confined space use self-contained breathing apparatus.

Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 469 - Protective clothing for firefighters. Standard EN 659 - Protective gloves for

firefighters

 $Standard\ EN\ 137-Self-contained\ open-circuit\ compressed\ air\ breathing\ apparatus\ with\ full\ face$

mask.

SECTION 6: Accidental release measures

$\underline{\textbf{6.1. Personal precautions, protective equipment and emergency procedures}}$

For non-emergency personnel : Act in accordance with local emergency plan.

Try to stop release. Evacuate area.

Ensure adequate air ventilation.

Stay upwind.

See section 8 of the SDS for more information on personal protective equipment.

For emergency responders : Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be

safe.

Oxygen detectors should be used when asphyxiating gases may be released.

See section 5.3 of the SDS for more information.

Safety Data Sheet

Helium

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 SDS Reference Number: EST-He-061A

6.2. Environmental precautions

Try to stop release.

6.3. Methods and material for containment and cleaning up

Ventilate area.

6.4. Reference to other sections

See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safe use of the product : Use only properly specified equipment which is suitable for this product, its supply pressure and

temperature. Contact your gas supplier if in doubt.

Do not smoke while handling product.

Avoid suck back of water, acid and alkalis.

Only experienced and properly instructed persons should handle gases under pressure. Ensure the complete gas system was (or is regularily) checked for leaks before use.

The product must be handled in accordance with good industrial hygiene and safety procedures.

Consider pressure relief device(s) in gas installations.

Do not breathe gas.

Avoid release of product into work area.

Do not allow backfeed into the container.

Safe handling of the gas receptacle : Do not allow backfeed into the container.

Protect containers from physical damage; do not drag, roll, slide or drop.

When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to

transport cylinders.

Leave valve protection caps, when provided, in place until the container has been secured against

either a wall or bench or placed in a container stand and is ready for use.

If user experiences any difficulty operating valve discontinue use and contact supplier.

Never attempt to repair or modify container valves or safety relief devices.

Damaged valves should be reported immediately to the supplier.

Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is

disconnected from equipment.

Close container valve after each use and when empty, even if still connected to equipment.

Never attempt to transfer gases from one cylinder/container to another.

Never use direct flame or electrical heating devices to raise the pressure of a container.

Do not remove or deface labels provided by the supplier for the identification of the content of the

container.

Suck back of water into the container must be prevented.

Open valve slowly to avoid pressure shock.

7.2. Conditions for safe storage, including any incompatibilities

Observe all regulations and local requirements regarding storage of containers.

Containers should not be stored in conditions likely to encourage corrosion.

Container valve guards or caps, when provided, should be in place.

Containers should be stored in the vertical position and properly secured to prevent them from

falling over.

Stored containers should be periodically checked for general condition and leakage.

Keep container below 50°C in a well ventilated place.

Store containers in location free from fire risk and away from sources of heat and ignition.

Keep away from combustible materials.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL (Occupational Exposure Limits) : None available.

DNEL (Derived-No Effect Level) : None available.

PNEC (Predicted No-Effect Concentration) : None available.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Systems under pressure should be regularily checked for leakages.

Oxygen detectors should be used when asphyxiating gases may be released. Consider the use of a work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, e.g. personal protective equipment

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following

recommendations should be considered:

PPE compliant to the recommended EN/ISO standards should be selected.

Safety Data Sheet

Helium

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 SDS Reference Number: EST-He-061A

• Eye/face protection : Wear safety glasses with side shields.

Standard EN 166 - Personal eye-protection - specifications.

Standard EN ISO 16321-1 - Eye and face protection for occupational use Part 1: General

requirements.

• Skin protection

- Other

Hand protection
 Wear working gloves when handling gas containers.

Standard EN 388 - Protective gloves against mechanical risks, performance level 1 or higher. Recommended types include wrist gloves from leather or synthetic material with equivalent

performance, fabric gloves, fabric gloves with leather palms.

: Wear safety shoes while handling containers.

Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

Respiratory protection
 Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in

oxygen-deficient atmospheres.

Self contained breathing apparatus is recommended, where unknown exposure may be expected,

e.g. during maintenance activities on installation systems.

Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face

mask

• Thermal hazards : None in addition to the above sections.

8.2.3. Environmental exposure controls

None necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

 Physical state at 20°C / 101.3kPa Gas. - Colour Colourless. Odour Odourless. Melting point / Freezing point -272 °C **Boiling** point -269 °C Flammability Non flammable. Lower explosion limit Not applicable. Not applicable. Upper explosion limit

Flash point : Not applicable for gases and gas mixtures.

Auto-ignition temperature : Non flammable. Decomposition temperature : Not applicable.

pH : Not applicable for gases and gas mixtures.

Viscosity, kinematic : No reliable data available.

Water solubility [20°C] : 1.5 mg/l

Partition coefficient n-octanol/water (Log Kow) : Not applicable for inorganic products.

Vapour pressure [20°C] : Not applicable. Vapour pressure [50°C] : Not applicable.

Density and/or relative density : Not applicable for gases and gas mixtures.

Relative vapour density (air=1) : 0.14

Particle characteristics : Not applicable for gases and gas mixtures.

Nanoforms are not relevant for gases and gas mixtures.

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Oxidising properties : No oxidising properties.

Critical temperature [°C] : -268 °C

9.2.2. Other safety characteristics

Molar mass : 4 g/mol

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Avoid moisture in installation systems.

10.5. Incompatible materials

For additional information on compatibility refer to ISO 11114.

10.6. Hazardous decomposition products

None.

Elme Messer Gaas AS Kopli 103 11712 Tallinn Estonia, +372 6102001 EE - en

4/7

Safety Data Sheet

Helium

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 SDS Reference Number: EST-He-061A

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

: No known toxicological effects by inhalation from this product. Acute toxicity

: No known effects from this product. Skin corrosion/irritation Serious eye damage/irritation : No known effects from this product. Respiratory or skin sensitisation : No known effects from this product. Germ cell mutagenicity : No known effects from this product. : No known effects from this product. Carcinogenicity : No known effects from this product. Toxic for reproduction: Fertility Toxic for reproduction : unborn child : No known effects from this product. STOT-single exposure : No known effects from this product. STOT-repeated exposure No known effects from this product.

Aspiration hazard Not applicable for gases and gas mixtures.

11.2. Information on other hazards

Other information : The substance/mixture has no endocrine disrupting properties

SECTION 12: Ecological information

12.1. Toxicity

: No ecological damage caused by this product. Assessment

EC50 48h - Daphnia magna [mg/l] No data available. EC50 72h - Algae [mg/l] No data available. LC50 96 h - Fish [mg/l] No data available.

12.2. Persistence and degradability

Assessment : No ecological damage caused by this product.

12.3. Bioaccumulative potential

Assessment : No ecological damage caused by this product.

12.4. Mobility in soil Assessment : No ecological damage caused by this product.

12.5. Results of PBT and vPvB assessment

: Not classified as PBT or vPvB. Assessment

12.6. Endocrine disrupting properties

: The substance/mixture has no endocrine disrupting properties. Assessment

12.7. Other adverse effects Other adverse effects

: Not classified as PMT or vPvM. Effect on the ozone laver No effect on the ozone layer.

Effect on global warming None.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Do not discharge into any place where its accumulation could be dangerous.

May be vented to atmosphere in a well ventilated place. Return unused product in original container to supplier.

List of hazardous waste codes (from Commission

Decision 2000/532/EC as amended)

: 16 05 05 : Gases in pressure containers other than those mentioned in 16 05 04.

: HELIUM, COMPRESSED

13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

SECTION 14: Transport information

14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN

: 1046 14.2. UN proper shipping name

Transport by road/rail/inland waterways

(ADR/RID/ADN)

Transport by air (ICAO-TI / IATA-DGR) Helium, compressed HELIUM, COMPRESSED Transport by sea (IMDG)

14.3. Transport hazard class(es)

Labelling

2.2: Non flammable, non-toxic gases.

Elme Messer Gaas AS Kopli 103 11712 Tallinn Estonia, +372 6102001 EE - en

5/7

Safety Data Sheet

Helium

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 SDS Reference Number: EST-He-061A

Transport by road/rail/inland waterways

(ADR/RID/ADN)

Class : 2 Classification code : 1A Hazard identification number : 20

Tunnel Restriction : E - Passage forbidden through tunnels of category E

: None.

Transport by air (ICAO-TI / IATA-DGR)

Class / Div. (Sub. risk(s)) : 2.2

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.2
Emergency Schedule (EmS) - Fire : F-C
Emergency Schedule (EmS) - Spillage : S-V

14.4. Packing group

Transport by road/rail/inland waterways : Not applicable.

(ADR/RID/ADN)

Transport by air (ICAO-TI / IATA-DGR) : Not applicable. Transport by sea (IMDG) : Not applicable.

14.5. Environmental hazards

Transport by road/rail/inland waterways

(ADR/RID/ADN)

Transport by air (ICAO-TI / IATA-DGR) : None.
Transport by sea (IMDG) : None.

14.6. Special precautions for user

Packing Instruction(s)

Transport by road/rail/inland waterways : P200.

(ADR/RID/ADN)

Transport by air (ICAO-TI / IATA-DGR)

Passenger and Cargo Aircraft : 200. Cargo Aircraft only : 200. Transport by sea (IMDG) : P200.

Special transport precautions

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the

event of an accident or an emergency.
Before transporting product containers:
- Ensure there is adequate ventilation.
- Ensure that containers are firmly secured.
- Ensure valve is closed and not leaking.

- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

Restrictions on use : None

Other information, restriction and prohibition : Not listed on the PIC list (Regulation EU 649/2012). regulations : Not listed on the POP list (Regulation EU 2019/1021).

Seveso Directive: 2012/18/EU (Seveso III) : Not covered.

National regulations

Regulatory reference : Ensure all national/local regulations are observed.

15.2. Chemical safety assessment

A CSA does not need to be carried out for this product.

SECTION 16: Other information

Indication of changes : Revised safety data sheet in accordance with commission regulation (EU) No 2020/878.

Safety Data Sheet

Helium

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 SDS Reference Number: EST-He-061A

Ahhre	viations	and	acronyms

: ATF - Acute Toxicity Estimate.

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008.

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.

EINECS - European Inventory of Existing Commercial Chemical Substances.

CAS# - Chemical Abstract Service number.

PPE - Personal Protection Equipment.

LC50 - Lethal Concentration to 50 % of a test population.

RMM - Risk Management Measures.

PBT - Persistent, Bioaccumulative and Toxic. vPvB - Very Persistent and Very Bioaccumulative.

STOT- SE: Specific Target Organ Toxicity - Single Exposure.

CSA - Chemical Safety Assessment.

EN - European Standard.

UN - United Nations.

ADR - Agreement concerning the International Carriage of Dangerous Goods by Road.

IATA - International Air Transport Association.

IMDG code - International Maritime Dangerous Goods.

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail.

WGK - Water Hazard Class.

STOT - RE: Specific Target Organ Toxicity - Repeated Exposure.

UFI: Unique Formula Identifier.

ADN -International Carriage of Dangerous Goods by Inland Waterways.

PROC -Process category

ERC – Environmental release category. PMT - Persistent, Mobile and Toxic. vPvM – very Persistent and very Mobile.

Training advice

The hazard of asphyxiation is often overlooked and must be stressed during operator training.

For more guidance, refer to EIGA SL 01 "Dangers of Asphyxiation", downloadable at

http://www.eiga.eu..

Further information Classification in accordance with the procedures and calculation methods of Regulation (EC)

1272/2008 (CLP).

Key literature references and sources of data are maintained in EIGA doc 169: 'Classification and

Labelling Guide', downloadable at http://www.Eiga.eu.

Full text of H- and EUH-statements		
Press. Gas (Comp.)	Gases under pressure : Compressed gas	
H280	Contains gas under pressure; may explode if heated.	

DISCLAIMER OF LIABILITY

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document