Safety Data Sheet

Nitrous oxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SDS Reference Number: EST-N2O-093A

Issue date: 2/15/2023 Revision date: 6/17/2025 Supersedes version of: 2/15/2023 Version: 2.0

Danger



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : Nitrous oxide
SDS no : EST-N2O-093A
Other means of identification : Nitrous oxide

CAS-No. : 10024-97-2 EC-No. : 233-032-0

EC Index-No. : ---

REACH registration No : 01-2119970538-25

Chemical formula : N2O

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : See the list of identified uses and exposure scenarios in the annex of the safety data sheet.

Perform risk assessment prior to use.

Uses advised against : Do not inhale product on purpose because of the risk of asphyxiation.

Do not inhale product on purpose because of the risk of narcotic effects.

Uses other than those listed above are not supported, contact your supplier for more information

on other uses.

Medicinal Gas for inhalation use.

1.3. Details of the supplier of the safety data sheet

Elme Messer Gaas AS Kopli 103

11712 Tallinn Estonia

T +372 6102001

info@elmemesser.ee, www.elmemesser.ee

1.4. Emergency telephone number

Emergency telephone number : Mürgistusteabekeskus, Terviseamet: tel. 16662, (24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards Oxidising Gases, Category 1 H270

Gases under pressure : Liquefied gas H280

Health hazards Specific target organ toxicity – Single exposure, Category 3, H336

Narcosis

Safety Data Sheet

Nitrous oxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 SDS Reference Number: EST-N2O-093A

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP) : Danger

Hazard statements (CLP) : H270 - May cause or intensify fire; oxidiser.

H280 - Contains gas under pressure; may explode if heated.

H336 - May cause drowsiness or dizziness.

Precautionary statements (CLP)

- Prevention : P260 - Do not breathe gas, vapours.

P244 - Keep valves and fittings free from oil and grease.

P220 - Keep away from clothing and other combustible materials.

- Response : P304+P340+P315 - IF INHALED : Remove person to fresh air and keep comfortable for breathing.

Get immediate medical advice.

P370+P376 - In case of fire: Stop leak if safe to do so.

- Storage : P403 - Store in a well-ventilated place.

Supplemental information : Do not inhale product on purpose because of the risk of asphyxiation.

Do not inhale product on purpose because of the risk of narcotic effects.

2.3. Other hazards

Contact with liquid may cause cold burns/frostbite.

Not classified as PBT or vPvB.

The substance/mixture has no endocrine disrupting properties.

Not classified as PMT or vPvM.

SECTION 3: Composition/information on ingredients

3.1. Substances

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] ATE, EUH-statements, M-Factors |
|---------------|---|-----|--|
| Nitrous oxide | CAS-No.: 10024-97-2 | 100 | Ox. Gas 1, H270 |
| | EC-No.: 233-032-0 | | Press. Gas (Liq.), H280 |
| | EC Index-No.: | | STOT SE 3, H336 |
| | REACH registration No: 01-2119970538-25 | | |

Contains no other components or impurities which will influence the classification of the product.

3.2. Mixtures Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim

warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.

- Skin contact : In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical

assistance.

- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.

Safety Data Sheet

Nitrous oxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 SDS Reference Number: EST-N2O-093A

- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

In low concentrations may cause narcotic effects. Symptoms may include dizziness, headache,

nausea and loss of co-ordination.

See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media Water spray or fog.

Product does not burn, use fire control measures appropriate for the surrounding fire.

- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

Specific hazards : Supports combustion.

Exposure to fire may cause containers to rupture/explode.

Hazardous combustion products : Nitric oxide/nitrogen dioxide.

5.3. Advice for firefighters

Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation

> may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage

If possible, stop flow of product.

Use water spray or fog to knock down fire fumes if possible.

Move containers away from the fire area if this can be done without risk.

Special protective equipment for fire fighters : Wear gas tight chemically protective clothing in combination with self contained breathing

apparatus.

Standard EN 943-2: Protective clothing against liquid and gaseous chemicals, aerosols and solid

particles. Gas-tight chemical protective suits for emergency teams.

Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face

mask.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

: Act in accordance with local emergency plan. For non-emergency personnel

> Try to stop release. Evacuate area.

Eliminate ignition sources. Ensure adequate air ventilation.

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be

dangerous Stay upwind.

See section 8 of the SDS for more information on personal protective equipment.

Monitor concentration of released product. For emergency responders

Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be

See section 5.3 of the SDS for more information.

6.2. Environmental precautions

Try to stop release.



Safety Data Sheet

Nitrous oxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 SDS Reference Number: EST-N2O-093A

6.3. Methods and material for containment and cleaning up

Ventilate area.

6.4. Reference to other sections

See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safe use of the product

: Use no oil or grease.

Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.

Do not smoke while handling product.

Keep equipment free from oil and grease. For more guidance, refer to the EIGA Doc. 33 - Cleaning of Equipment for Oxygen Service downloadable at http://www.eiga.eu.

Avoid suck back of water, acid and alkalis.

Only experienced and properly instructed persons should handle gases under pressure.

Ensure the complete gas system was (or is regularily) checked for leaks before use.

of Nitrous oxide", downloadable at http://www.eiga.org." and consult your supplier.

The product must be handled in accordance with good industrial hygiene and safety procedures. Consider pressure relief device(s) in gas installations.

For more guidance on safe use, refer to the EIGA Doc.176 "Safe practices for storage and handling

Do not breathe gas.

Avoid release of product into work area.

Temperatures above 150°C (300°F) shall be avoided by all practical means, to reduce the likelihood of an explosive decomposition of the nitrous oxide.

Clean all surfaces in direct contact with nitrous oxide as for oxygen service.

Nitrous oxide transfer pumps shall be provided with an interlock to prevent dry running. Use self-limiting heating devices. Direct contact electric immersion heaters are not allowed.

Use only lubricants and sealings approved for the specific gas service.

: Do not allow backfeed into the container.

Protect containers from physical damage; do not drag, roll, slide or drop.

When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.

Leave valve protection caps, when provided, in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.

If user experiences any difficulty operating valve discontinue use and contact supplier.

Never attempt to repair or modify container valves or safety relief devices.

Damaged valves should be reported immediately to the supplier.

Keep container valve outlets clean and free from contaminants particularly oil and water.

Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.

Close container valve after each use and when empty, even if still connected to equipment.

Never attempt to transfer gases from one cylinder/container to another.

Never use direct flame or electrical heating devices to raise the pressure of a container.

Do not remove or deface labels provided by the supplier for the identification of the content of the

Suck back of water into the container must be prevented.

Open valve slowly to avoid pressure shock.

Safe handling of the gas receptacle

Safety Data Sheet

Nitrous oxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 SDS Reference Number: EST-N2O-093A

7.2. Conditions for safe storage, including any incompatibilities

Store locked up.

Segregate from flammable gases and other flammable materials in store.

Observe all regulations and local requirements regarding storage of containers.

Containers should not be stored in conditions likely to encourage corrosion.

Container valve guards or caps, when provided, should be in place.

Containers should be stored in the vertical position and properly secured to prevent them from

falling over.

Stored containers should be periodically checked for general condition and leakage.

Keep container below 50°C in a well ventilated place.

Store containers in location free from fire risk and away from sources of heat and ignition.

Keep away from combustible materials.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Nitrous oxide (10024-97-2) | | |
|--|--|--|
| Estonia - Occupational Exposure Limits | | |
| Local name | Dilämmastikoksiid (naerugaas) | |
| OEL TWA | 180 mg/m³ | |
| | 100 ppm | |
| OEL STEL | 900 mg/m³ | |
| | 500 ppm | |
| Regulatory reference | Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 02.04.2024, 13) | |

| Nitrous oxide (10024-97-2) | | |
|--|-----------|--|
| DNEL: Derived no effect level (Workers) | | |
| Long-term - systemic effects, inhalation | 183 mg/m³ | |

PNEC (Predicted No-Effect Concentration) : None established.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Product to be handled in a closed system.

Systems under pressure should be regularily checked for leakages.

Ensure exposure is below occupational exposure limits (where available).

Gas detectors should be used when oxidising gases may be released.

Consider the use of a work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, e.g. personal protective equipment

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:

PPE compliant to the recommended EN/ISO standards should be selected.

Safety Data Sheet

Nitrous oxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 SDS Reference Number: EST-N2O-093A

• Eye/face protection : Wear goggles when transfilling or breaking transfer connections.

Standard EN 166 - Personal eye-protection - specifications.

Standard EN ISO 16321-1 - Eye and face protection for occupational use Part 1: General

requirements.

• Skin protection

- Other

- Hand protection : Wear working gloves when handling gas containers.

Standard EN 388 - Protective gloves against mechanical risks, performance level 1 or higher. Recommended types include wrist gloves from leather or synthetic material with equivalent

performance, fabric gloves, fabric gloves with leather palms.

Wear cold insulating gloves when transfilling or breaking transfer connections.

Standard EN 511 - Cold insulating gloves, performance level 1 or higher. Recommended types include insulated gauntlets or gloves specifically selected to prevent liquid penetration and ingress

of cryogenic liquids and to provide mechanical resistance.

Standard EN ISO 14116 - Limited flame spread materials.

Wear safety shoes while handling containers.

Consider the use of flame resistant safety clothing.

Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

• Respiratory protection : Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in

oxygen-deficient atmospheres.

Self contained breathing apparatus is recommended, where unknown exposure may be expected,

e.g. during maintenance activities on installation systems.

Keep self contained breathing apparatus readily available for emergency use.

 $Standard\ EN\ 137-Self-contained\ open-circuit\ compressed\ air\ breathing\ apparatus\ with\ full\ face$

mask.

Consult respiratory device supplier's product information for the selection of the appropriate

device.

• Thermal hazards : None in addition to the above sections.

8.2.3. Environmental exposure controls

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific

methods for waste gas treatment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

- Physical state at 20°C / 101.3kPa- Colour: Gas.- Colourless.

Odour : Sweetish. Poor warning properties at high concentrations.

Flash point : Not applicable for gases and gas mixtures.

Auto-ignition temperature : Non flammable.

Decomposition temperature : Not applicable.

pH : Not applicable for gases and gas mixtures.

Viscosity, kinematic : No reliable data available.

Water solubility [20°C] : 1500 mg/l
Partition coefficient n-octanol/water (Log Kow) : 0.4
Vapour pressure [20°C] : 50.8 bar(a)
Vapour pressure [50°C] : Not applicable.

Density and/or relative density : Not applicable for gases and gas mixtures.

Relative vapour density (air=1) : 1.5

Safety Data Sheet

Nitrous oxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 SDS Reference Number: EST-N2O-093A

Particle characteristics : Not applicable for gases and gas mixtures.

Nanoforms are not relevant for gases and gas mixtures.

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Oxidising properties : Oxidiser. - Coefficient of oxygen equivalency (Ci) : 0.6 Critical temperature [°C] : 36.4 °C

9.2.2. Other safety characteristics

Molar mass : 44 g/mol

Other data Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

At temperatures over 575°C and at atmospheric pressure, nitrous oxide decomposes into nitrogen

and oxygen.

In the presence of catalysts (e.g. halogen products, mercury, nickel, platinum) the rate of decomposition increases and decomposition can occur at even lower temperatures.

Nitrous oxide dissociation is irreversible and exothermic, leading to a considerable rise in pressure.

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Violently oxidises organic material.

10.4. Conditions to avoid

Avoid moisture in installation systems.

10.5. Incompatible materials

Keep equipment free from oil and grease. For more guidance, refer to the EIGA Doc. 33 - Cleaning of

Equipment for Oxygen Service downloadable at http://www.eiga.eu.

May react violently with combustible materials. May react violently with reducing agents.

For additional information on compatibility refer to ISO 11114.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be

produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

: No additional information available Acute toxicity

| Nitrous oxide (10024-97-2) | |
|-----------------------------|---------------|
| LC50 Inhalation - Rat [ppm] | 500000 ppm/4h |

Skin corrosion/irritation : No known effects from this product. : No known effects from this product. Serious eye damage/irritation Respiratory or skin sensitisation : No known effects from this product.

Safety Data Sheet

Nitrous oxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 SDS Reference Number: EST-N2O-093A

Germ cell mutagenicity : No known effects from this product. : No known effects from this product. Carcinogenicity Toxic for reproduction: Fertility : No known effects from this product. Toxic for reproduction: unborn child No known effects from this product. STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : Hemotoxic effect.

> Neurologic effect. At low concentrations:

: Central nervous system. Target organ(s)

> Erythrocytes. Kidneys. liver.

Aspiration hazard : Not applicable for gases and gas mixtures.

11.2. Information on other hazards

Other information : Inhalation causes narcotic effects.

The substance/mixture has no endocrine disrupting properties.

SECTION 12: Ecological information

12.1. Toxicity

Assessment : No ecological damage caused by this product.

EC50 48h - Daphnia magna [mg/l] No data available. EC50 72h - Algae [mg/l] No data available. LC50 96 h - Fish [mg/l] : No data available.

12.2. Persistence and degradability

Assessment : Not applicable for inorganic products. Study scientifically unjustified.

12.3. Bioaccumulative potential

: Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Assessment

See section 9.

12.4. Mobility in soil

Assessment : Because of its high volatility, the product is unlikely to cause ground or water pollution.

Partition into soil is unlikely.

12.5. Results of PBT and vPvB assessment

: Not classified as PBT or vPvB. Assessment

12.6. Endocrine disrupting properties

Assessment : The substance/mixture has no endocrine disrupting properties.

12.7. Other adverse effects

Other adverse effects : Not classified as PMT or vPvM. Effect on the ozone layer : No effect on the ozone layer.

Global warming potential [CO2=1]

Effect on global warming When discharged in large quantities may contribute to the greenhouse effect.

Contains greenhouse gas(es).

Safety Data Sheet

Nitrous oxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 SDS Reference Number: EST-N2O-093A

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Discharge to atmosphere in large quantities should be avoided.

Contact supplier if guidance is required.

Ensure that the emission levels from local regulations or operating permits are not exceeded. Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at http://www.eiga.eu

for more guidance on suitable disposal methods.

Do not discharge into any place where its accumulation could be dangerous.

Return unused product in original container to supplier.

List of hazardous waste codes (from Commission

Decision 2000/532/EC as amended)

: 16 05 04 *: Gases in pressure containers (including halons) containing hazardous substances.

13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

SECTION 14: Transport information

14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN

UN-No. : 1070

14.2. UN proper shipping name

Transport by road/rail/inland waterways

(ADR/RID/ADN)

: NITROUS OXIDE

Transport by air (ICAO-TI / IATA-DGR) : Nitrous oxide
Transport by sea (IMDG) : NITROUS OXIDE

14.3. Transport hazard class(es)

Labelling :



2.2 : Non flammable, non-toxic gases.

5.1: Oxidizing substances.

Transport by road/rail/inland waterways (ADR/RID/ADN)

Class : 2
Classification code : 20
Hazard identification number : 25

Tunnel Restriction : C/E - Tank carriage : Passage forbidden through tunnels of category C, D and E. Other carriage :

Passage forbidden through tunnels of category E

Transport by air (ICAO-TI / IATA-DGR)

Class / Div. (Sub. risk(s)) : 2.2 (5.1)

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)): 2.2 (5.1)Emergency Schedule (EmS) - Fire: F-CEmergency Schedule (EmS) - Spillage: S-W

14.4. Packing group

Transport by road/rail/inland waterways

(ADR/RID/ADN)

: Not applicable.

Transport by air (ICAO-TI / IATA-DGR) : Not applicable.

Transport by sea (IMDG) : Not applicable.

Safety Data Sheet

Nitrous oxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 SDS Reference Number: EST-N2O-093A

14.5. Environmental hazards

Transport by road/rail/inland waterways

(ADR/RID/ADN)

: None.

Transport by air (ICAO-TI / IATA-DGR) : None.
Transport by sea (IMDG) : None.

14.6. Special precautions for user

Packing Instruction(s)

Transport by road/rail/inland waterways : P200.

(ADR/RID/ADN)

Transport by air (ICAO-TI / IATA-DGR)

Passenger and Cargo Aircraft : 200.
Cargo Aircraft only : 200.
Transport by sea (IMDG) : P200.

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the

event of an accident or an emergency.

Before transporting product containers:
- Ensure there is adequate ventilation.
- Ensure that containers are firmly secured.
- Ensure valve is closed and not leaking.

- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.

- Ensure valve protection device (where provided) is correctly fitted.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

Restrictions on use : None.

Other information, restriction and prohibition : Not listed on the PIC list (Regulation EU 649/2012). regulations : Not listed on the POP list (Regulation EU 2019/1021).

Seveso Directive: 2012/18/EU (Seveso III) : Covered.

National regulations

Regulatory reference : Ensure all national/local regulations are observed.

15.2. Chemical safety assessment

A CSA has been carried out.

SECTION 16: Other information

Indication of changes : Revised safety data sheet in accordance with commission regulation (EU) No 2020/878.

| Section | Changed item | Comments |
|---------|--------------|----------|
| | Company | Added |



Safety Data Sheet

Nitrous oxide

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 SDS Reference Number: EST-N2O-093A

Abbreviations and acronyms

: ATE - Acute Toxicity Estimate.

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008.

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.

EINECS - European Inventory of Existing Commercial Chemical Substances.

CAS# - Chemical Abstract Service number.

PPE - Personal Protection Equipment.

LC50 - Lethal Concentration to 50 % of a test population.

RMM - Risk Management Measures.

PBT - Persistent, Bioaccumulative and Toxic.

vPvB - Very Persistent and Very Bioaccumulative.

STOT- SE: Specific Target Organ Toxicity - Single Exposure.

CSA - Chemical Safety Assessment.

EN - European Standard.

UN - United Nations.

ADR - Agreement concerning the International Carriage of Dangerous Goods by Road.

IATA - International Air Transport Association.

IMDG code - International Maritime Dangerous Goods.

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail.

WGK - Water Hazard Class.

STOT - RE: Specific Target Organ Toxicity - Repeated Exposure.

UFI: Unique Formula Identifier.

ADN -International Carriage of Dangerous Goods by Inland Waterways.

PROC -Process category

•

ERC – Environmental release category.

PMT - Persistent, Mobile and Toxic.

vPvM – very Persistent and very Mobile.

: None.

Classification in accordance with the procedures and calculation methods of Regulation (EC)

1272/2008 (CLP).

 $\label{thm:continuous} \text{Key literature references and sources of data are maintained in EIGA doc 169: 'Classification and all the continuous continuous$

Labelling Guide', downloadable at http://www.Eiga.eu .

| Full text of H- and EUH-statements | | |
|------------------------------------|--|--|
| Ox. Gas 1 | Oxidising Gases, Category 1 | |
| Press. Gas (Liq.) | Gases under pressure : Liquefied gas | |
| STOT SE 3 | Specific target organ toxicity – Single exposure, Category 3, Narcosis | |
| H270 | May cause or intensify fire; oxidiser. | |
| H280 | Contains gas under pressure; may explode if heated. | |
| Н336 | May cause drowsiness or dizziness. | |

DISCLAIMER OF LIABILITY

Training advice

Further information

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press.

Whilst proper care has been taken in the preparation of this document, no liability for injury or

damage resulting from its use can be accepted.

End of document